

09/074012

3/30/99  
Linda  
B.

## DESCRIPTION

## HIGH THERMAL CONDUCTIVITY COMPOSITE MAGNETIC BODY

## Technical Field

The present invention relates to a composite magnetic body comprising soft magnetic powder mixed with an organic binding agent and, in particular, to a composite magnetic body which is excellent in thermal conductivity.

## Background Art

An electromagnetic interference suppressing body is used for suppressing electromagnetic interference caused by interference of undesired electromagnetic waves.

Conventionally, for blocking invasion of the external undesired electromagnetic waves into an electronic device, shielding of the electronic device by a conductor has been carried out. However, since the blocking of the electromagnetic waves by the conductor aims to reflect the electromagnetic waves, radiant waves from a certain component within the electronic device may be reflected to adversely affect other components in the same electronic device as secondary noise. Particularly, following reduction in size and use of the higher frequency of electronic devices in recent years, problems of the interference due to the external electromagnetic waves and of the secondary noise due to the internal electromagnetic waves are serious.

00041-050598

JP-A-7-212079 discloses a composite magnetic body which can suppress interference of undesired electromagnetic waves utilizing absorption of high-frequency waves due to a complex permeability of a soft magnetic body of a certain kind. This composite magnetic body is constituted of a composite magnetic sheet comprising soft magnetic powder mixed with an organic binding agent.

The sheet of the composite magnetic body may be used as it is. On the other hand, by forming a structure stacked with a conductive sheet, the coming electromagnetic waves are absorbed by the composite magnetic sheet and the electromagnetic waves passing through the composite magnetic sheet are reflected by the conductive sheet into the composite magnetic sheet, so as to suppress the interference of the undesired electromagnetic waves.

Such an electromagnetic interference suppressing body is disposed, for example, on the surface of an electronic device or around an electronic component in the electronic device which is liable to suffer an influence of the external electromagnetic waves. Alternatively, it is used so as to be disposed between two printed circuit boards each mounted thereon with electronic components and confronting each other with a space therebetween.

Incidentally, there is a problem that since the organic binding agent used in formation of the composite magnetic body is liable to be influenced by heat to cause

2025 RELEASE UNDER E.O. 14176

deformation, degradation or the like, it can not be used in contact with an electronic component which generates much heat.

Further, there is a problem that since the organic binding agent is poor in thermal conductivity, it prevents heat dissipation from an electronic component having a large calorific value.

Therefore, an object of the present invention is to provide a composite magnetic body having a high thermal conductivity and being hardly influenced by heat, and an electromagnetic interference suppressing body using the composite magnetic body.

Another object of the present invention is to provide a heat dissipation sheet and a heat sink each using a composite magnetic body having a high thermal conductivity.

#### Disclosure of the Invention

*disclosed and claimed herein*  
As recited in claim 1, the present invention provides a composite magnetic body comprising soft magnetic powder dispersed in an organic binding agent which is characterized in that heat conductive powder is further dispersed into the organic binding agent, thereby the composite magnetic body having a high thermal conductivity.

As preferable one of the heat conductive powder, at least one kind of powder selected from the group of alumina ( $\text{Al}_2\text{O}_3$ ) powder, aluminum nitride ( $\text{AlN}$ ) powder, cubic boron nitride ( $\text{BN}$ ) powder, insulating silicon carbide ( $\text{SiC}$ )

00074012-050508

powder and a heat conductive reinforcement (capton) powder, as recited in ~~claim 2~~, <sup>the claims</sup> can be cited.

As the organic binding agent, thermoplastic resin having a glass transition temperature of not less than 120°C is preferable ~~as recited in claim 3~~, and typically, thermoplastic polyimide or liquid crystal polymer can be ~~cited as recited in claim 4~~. <sup>disclosed and claimed herein</sup>

As recited in claim 5, such a high thermal conductivity composite magnetic body may be stacked with a conductive support to be used as an electromagnetic interference suppressing body.

Further, such a high thermal conductivity composite magnetic body can also be used as a heat dissipation sheet for an electronic device as ~~recited in claim 6~~, <sup>claimed herein</sup> or can constitute a heat sink working also for electromagnetic interference suppression ~~as recited in claim 7~~.

Further, according to the present invention, as ~~recited in claims 8 and 9~~, a heat-resistive composite magnetic body can be provided.

#### Brief Description of the Drawings

Fig. 1 is a schematic sectional view showing an embodiment of a composite magnetic body of the present invention.

Fig. 2 is a schematic sectional view showing an electromagnetic interference suppressing body using the composite magnetic body of Fig. 1.

Fig. 3 is a side view of an electronic device, wherein the composite magnetic body shown in Fig. 1 is used as a heat dissipation sheet and attached to an IC package along with a heat sink.

Fig. 4 shows an IC package attached with a heat dissipation sheet made of the composite magnetic body shown in Fig. 1, along with a heat sink, wherein (a) is a side view thereof and (b) is a plan view of the heat dissipation sheet.

Fig. 5 is a side view showing an IC package attached with a heat dissipation sheet made of the composite magnetic body shown in Fig. 1, along with a radiator utilizing a heat pipe.

Fig. 6 is a perspective view showing a switching device attached with a heat dissipation sheet of the composite magnetic body shown in Fig. 1, along with a heat sink.

Fig. 7 is a perspective view showing a switching device attached with a heat sink made of the composite magnetic body shown in Fig. 1.

Figs. 8(a), (b) and (c) are perspective views showing different structures of heat sinks using the composite magnetic body shown in Fig. 1, as heat sinks for IC packages.

Fig. 9 is a side view of an IC package attached with the heat sink of Fig. 8(c).

Figs. 10(a) and (b) are a side view of an IC package attached with a heat sink of another type and a plan view

2025 RELEASE UNDER E.O. 14176

[illegible][illegible][illegible][illegible][illegible][illegible][illegible]

[illegible][illegible][illegible]

Referring to Fig. 2, an electromagnetic interference suppressing body 10 using the composite magnetic bodies 1 of Fig. 1 is shown. The electromagnetic interference suppressing body 10 has a stacked structure wherein the composite magnetic bodies 1 are stacked on both sides of an electrically conductive support 5. The electrically conductive support 5, although an example using one constituted of a textile of electrically conductive fiber is shown in the figure, may be constituted of an electric conductor thin plate, a electric conductor mesh plate, a soft magnetic metal plate, a soft magnetic metal mesh plate or a textile of soft magnetic metal fiber. It may also be arranged that a layer of the composite magnetic body 1 is provided on only one side of the electrically conductive support 5.

Since a structure itself of the electromagnetic interference suppressing body 10 and an electromagnetic interference suppressing operation thereof are disclosed in detail in JP-A-7-212079, explanation thereof is omitted with respect to the present invention.

Referring to Fig. 3, an IC package 12 is mounted on a circuit board 11 as an electronic component of active elements. For enhancing dissipation of generated heat of the IC package 12, a heat sink 13 is provided via the composite magnetic body 1. In this structure, the heat from the IC package 12 is conducted to the heat sink 8 through the composite magnetic body 1 excellent in thermal



As a heat dissipation sheet, the electromagnetic interference suppressing body 10 of Fig. 2 can be used instead of the composite magnetic body 1. For indicating this, in Fig. 3, reference sign 10 representing the electromagnetic interference suppressing body is shown in parentheses along with reference sign 1 representing the composite magnetic body.

Referring to Fig. 5, there is shown a structure where a heat dissipation sheet or a block 22, on the IC package 12, made of the composite magnetic body 1 of Fig. 1 is

Referring to Fig. 5, there is shown a structure where a heat dissipation sheet or a block 22, on the IC package 12, made of the composite magnetic body 1 of Fig. 1 is

formed with a hole into which a heat pipe 17 of a radiator 16 is inserted. In this structure, heat from the IC package is transmitted to the radiator 16 from the heat dissipation sheet 22 through the heat pipe 17 and radiated therefrom.

Referring to Fig. 6, there is shown an apparatus wherein a heat sink 19 with fins is attached to a switching element 18 via a heat dissipation sheet 23 made of the composite magnetic body 1 of Fig. 1.

A heat sink itself can be constituted of the composite magnetic body 1. Fig. 7 shows this example. In the same figure, a heat sink 30 constituted of the composite magnetic body 1 is directly attached to the switching element 18.

Fig. 8 shows various shapes of heat sinks constituted of the composite magnetic body 1. In the figure, (a) shows a heat sink 31 having a simple plate shape, (b) shows a U-shaped heat sink 32 provided with flanges at both ends of a plate, and (c) shows a heat sink 33 having a dish shape. These heat sinks are not only constituted of the composite magnetic body 1, but may also be constituted using the electromagnetic interference body of Fig. 2.

Fig. 9 is a side view showing the state wherein the heat sink 33 of Fig. 8(c) is attached to the IC package 12 by an adhesive 40. Also in this structure, the generated heat of the IC package 12 can be effectively radiated, and the radiation and invasion of the undesired electromagnetic waves can be prohibited.

Fig. 10 is a diagram showing still another structure of a heat sink using the composite magnetic body 1 of Fig. 1 or the electromagnetic interference suppressing body 10 of Fig. 2. As shown in (b) of the same figure, the heat sink 34 has a structure such that it is U-shaped in section and provided with many through-holes 35 extending from the obverse side to the reverse side thereof. In this structure, the dissipation of generated heat from the IC package 12 is promoted by the through-holes 35.

Hereinbelow, characteristics will be cited about examples of a composite magnetic body according to the present invention and a stacked structure of the composite magnetic body and a conductor.

First, a plate sample I shown at (a) in Fig. 11 was prepared, which was made of a composite magnetic body comprising soft magnetic powder, an organic binding agent and heat conductive powder at a composite ratio shown in Table 1. The size was set to 3.8 x 10.2 (cm).

Specifically, soft magnetic powder, an organic binding agent and heat conductive powder subjected to the coupling process were, at first, kneaded by a kneader and rolled by ~~parallelly disposed~~ <sup>through</sup> rolls <sup>in parallel relationship onto the other</sup> so as to produce a composite magnetic sheet with a thickness of 0.5mm. Then, two obtained sheets were stuck together to obtain the sample I with a thickness of 1mm having a structure as shown at (a) in Fig. 11.

Table 1

	Substance Name	Composite Ratio (Weight Parts)
Soft Magnetic Powder	Fe-Al-Si Alloy Mean Particle Diameter: 35 $\mu$ m Aspect Ratio: > 5	80
Coupling Agent	titanate	0.8
Organic Binding Agent	chlorinated polyethylene	15
Heat Conductive Powder	Al <sub>2</sub> O <sub>3</sub>	5

The obtained sample I was analyzed using a vibrating sample type magnetometer and a scanning electron microscope, and it was found that a magnetization easy axis and orientation of the magnetic particles are both in an in-surface direction of this layer.

The soft magnetic powder used herein was gas-phase oxidized in an atmosphere of N<sub>2</sub>-O<sub>2</sub> mixed gas at a 20% O<sub>2</sub> partial pressure, subjected to annealing in an atmosphere of Ar at 650°C for two hours, and formed with oxide films on the surfaces thereof.

The sheets 1 of the composite magnetic body obtained above and a copper thin plate 50 were stacked together to produce a sample II of a structure shown at (b) in Fig. 11. Specifically, the extremely thin copper plate with a thickness of 0.18mm was sandwiched on both sides thereof by the sheets of the composite magnetic body 1 and stacked together, and then rolled by the rolls to obtain the total

thickness of 1mm.

Further, as a comparative example, a sample III of a structure of Fig. 11(c) was prepared. Specifically, sheets of insulator 51 made of polyvinyl fluoride were stacked on both sides of an extremely thin copper plate 50 with a thickness of 0.18mm to obtain the total thickness of 0.3mm.

Then, about the samples I to III, the surface resistivity, the transmittance attenuation, the coupling attenuation and the heat dissipation amount were evaluated.

For measuring the transmittance attenuation and the coupling attenuation, an apparatus as shown in Figs. 12 and 13 was used wherein an electromagnetic wave radiating micro-loop antenna 63 and an electromagnetic field receiving micro-loop antenna 64 were connected to an electromagnetic wave generator 61 and an electromagnetic field strength measuring device 62, respectively. As shown in Fig. 12, the transmittance attenuation was measured by disposing a sample 65 between the electromagnetic wave radiating micro-loop antenna 63 and the electromagnetic field receiving micro-loop antenna 64.

On the other hand, as shown in Fig. 13, the coupling attenuation was measured by confronting the electromagnetic wave transmitting micro-loop antenna 63 and the electromagnetic field receiving micro-loop antenna 64 against the same side of the sample 65.

To the electromagnetic field strength measuring device 62, a spectrum analyzer, not shown, was connected. The measurement was carried out at frequencies 100 to

1000MHz, using as a reference an electromagnetic field strength in the state where the sample 65 was not present.

Using a silicon heat conductive adhesive tape (THERMATTACH produced by Taiyo Kanaami Co., Ltd.), the samples I to III were adhered to a semiconductor device. Using as a reference a state where no sample was present, the heat dissipation amount was expressed by a temperature difference ( $\Delta T$ ) relative to a sample temperature. The larger numeric value of the temperature difference represents the higher dissipation effect. The measurement condition was such that there was no air flow and the ambient temperature was 21 to 24°C.

The measurement results are shown in Table 2.

Table 2

	Thick- ness (mm)	Surface Resis- tivity ( $\Omega$ )	Transmit- tance Attenuation (dB)	Coupling Attenua- tion (dB)	Tempera- ture $\Delta T$ (°C)
Sam- I ple	1	$1 \times 10^8$	6 to 12	8 to 10	20
II	1	$1 \times 10^8$	40 to 55	2 to 3	45
III	0.3	$1 \times 10^{14}$	40 to 55	-8 to -10	24

From Table 2, it is seen that the composite magnetic body of the present invention and the one having the stacked structure of the composite magnetic body and the electric conductor (samples I and II) have characteristics more than equality as compared with the comparative sample (sample III). Further, in comparison between the samples I

and II, it is seen that the sample I is excellent in coupling attenuation while the sample II is excellent in heat dissipation amount.

#### Industrial Applicability

According to the present invention, since there can be obtained a composite magnetic body excellent in thermal resistance and thermal conductivity and having electromagnetic wave absorbing capability, it may be used as a heat dissipation sheet and/or a heat sink for an electronic component or device so as to promote heat dissipation while prohibiting radiation and invasion of undesired electromagnetic waves.

0007404-10059